

## Specification For Street Nameplates

NON REFLECTIVE STREET NAMEPLATE,  
DIE PRESSED ALUMINIUM  
11 GAUGE, 3½" KINDERSLEY ON 7" PLATE,  
½" BORDER, BLACK ON WHITE,  
RADIUSSED CORNERS, GREY BACK,  
DRILLED FOR POST MOUNTING

MOUNTED ON 2 NO 80MM X 80MM UPRIGHTS,  
BEVELLED TOPS, 30MM BACKING BOARD  
ALL IN RECYCLED PLASTIC  
BOLTED THROUGH, NAMEPLATE  
FIXED WITH SECURITY SCREWS  
FRAME TO INCLUDE BASE RODS

### **Street name plates – guidelines for positioning.**

Where possible, name plates should be positioned at 45 degrees to the "main" road, so that it can be read by approaching traffic.

If the road has equal amounts of traffic from both directions, two signs are to be used. If traffic only comes from one direction, only one sign need be used.

If there is a wall immediately to the rear of the path, mount the name plate on a suitable backing board, and fix to the wall.

If the name plate is to be post mounted, position the posts in the back of the footpath, *not* behind it. The reason for this is that the footpath is "public", but the verge will probably be private and a new owner could ask us to move it in order to either plant a hedge or build a wall.

These are merely guidelines and not definitive. If your circumstances are different please contact Anna Grieve on 01427 676620 to discuss the matter.